

# Split Wall Series

RC-ACD-H Model



Power Supply	Solar Power	V	DC90-380V MAX.15A		
	AC Power Connected	V	200-230V(50/60Hz)		
Cooling	Capacity	Btu/h	12000	18000	24000
	Inverter Capacity Range	Btu/h	3071-12966	3412-19449	4094-23200
	Power Input	kW	0.96	1.42	1.83
	Rated Current(AC)	A	4.35	6.1	8
	SEER		22	21	20
	EER		12.5	12.0	12.0
Heating	Capacity		12,000	17,200	22,000
	Inverter Capacity Range	Btu/h	3753~13306	4435~19789	5100~23542
	Power Input	kW	1.028	1.37	1.79
	Rated Current	A	5.9	5.9	8
	HSPF		11	10	11
	COP		12.28	12.39	12.28
	Dehumidification	pt/h	1.3L/h	1.9L/h	2.3L/h
Indoor Air Flow - (Hifan)		cfm	650	1100	1200
Indoor Noise dB(A) (Hifan)		dB(A)	41	48	49
Max Refrigeration Pipe Length		ft/m	15	15	15
Indoor Unit	Dimension(W*D*H)	mm	850*290*205	970*315*235	1100*330*235
	Packing(W*D*H)	mm	920*370*285	1045*385*320	1160*390*300
	Net/Gross Weight	kg	10/12.1	14/16.5	16/18
Outdoor Unit	Dimension(W*D*H)	mm	860*325*540	890*320*670	890*320*670
	Packing(W*D*H)	mm	920*395*605	1020*430*755	1020*430*755
	Net/Gross Weight	kg	32.0/36.0	48.0/53.0	48.0/53.0
Approvals	ETL/cETL/ AHRI Performance Certified 210/240				

